

Design Panel Stepwood® Balance / Stepwood® Balance Light (on fleece)

- Type of wood: Oak sanded , Walnut sanded, Spruce sanded
 others: _____
- Surface: unlacquered lacquered (with 1K-NC paint)
- Panel size: 1250 x 219mm (usable area: 0.252m²)
- Panel thickness: 15mm (carrier MDF), resp. 9mm (carrier fleece)
- Weight: Depending on type of wood (around. 4 kg/m²)
- Composition: solid wooden slats all 73mm width and different lengths and heights, interlocking borders left and right for a smooth interconnection
- Packaging amount: 1 box = 4 Panels = 1m², or all panels loose in a wooden packing case
- Bonding: White glue D3 DIN EN 204 (PVA glue, waterproof and formaldehyde-free)
- Lacquer: Transparent according to DIN 53160 part 1, 2: no discoloration (step 5); DIN 68861 Part 1C Formulation is free from: Wood preservatives, toxic heavy metals, phthalate plasticizers, formaldehyde, CMR substances Cat. 1A + 1B and volatile halogenated organic compounds.
- Installation type: Horizontal or vertical on walls or ceilings, furniture fronts
- Assembly: by means of claws and wooden framework (please see mounting accessories by KOLAR) or permanently elastic adhesive, glue
- Application: For interior use only,
use in the damp rooms is not recommended
- Production on demand, minimum order qty: 80 panels (20.16m²), delivery time approx. 35 working days

Manufacturer: Franz Kolar GmbH, www.kolar.at

Product offered: _____

Qty: _____m²

Mounting accessories for Stepwood®

- Claw set (SW.KR)
Mounting (SW.ML)
profile Skirting (SW.RL)

As of November 2020