

Specification text SW_Original

Design Panel Stepwood® Original

Stepwood® Original

Type of wood:	<input type="checkbox"/> Oak brushed, <input type="checkbox"/> Oak sanded , <input type="checkbox"/> Walnut sanded, <input type="checkbox"/> Beech heartwood sanded, <input type="checkbox"/> Spruce sanded, <input type="checkbox"/> Spruce brushed, <input type="checkbox"/> Oak limed (lacquered), <input type="checkbox"/> pinus cembra
Surface:	<input type="checkbox"/> unlacquered <input type="checkbox"/> lacquered (with 1K-NC paint)
Panel size:	1250 x 219mm
Panel thickness:	12mm
Weight:	Depending on type of wood (around. 9 kg/m ²)
Composition:	solid wooden slats in different widths and heights, on a MDF panel (thickness 6mm), grooved on all sides for mounting
Packaging amount:	1 box = 5 Panels = 1.37m ²
Bonding:	White glue D3 DIN EN 204 (waterproof and formaldehyde-free)
Lacquer:	Transparent according to DIN 53160 part 1, 2: no discoloration (step 5); DIN 68861 Part 1C Formulation is free from: Wood preservatives, toxic heavy metals, phthalate plasticizers, formaldehyde, CMR substances Cat. 1A + 1B and volatile halogenated organic compounds.
Installation type:	Horizontal or vertical on walls or ceilings, furniture fronts
Assembly:	by means of claws and wooden framework (please see mounting accessories by KOLAR) or permanently elastic adhesive
Application:	For interior use only, use in the damp rooms is not recommended

Manufacturer: Franz Kolar GmbH, www.kolar.at

Product offered: _____

Qty: _____m²

Mounting accessories for Stepwood®

Claw set	(SW.KR)
Mounting profile	(SW.ML)
Skirting	(SW.RL)

As of November 2020