

## WALLWOOD

Type of wood:	<input type="checkbox"/> oak reclaimed lumber, <input type="checkbox"/> silver oak , <input type="checkbox"/> joist oak light, <input type="checkbox"/> oak sunburnt
Surface:	<input type="checkbox"/> unlacquered <input type="checkbox"/> lacquered (with 1K-NC paint)
Panel size:	1250 x 219mm
Panel thickness:	14.5mm
Weight:	around. 9 kg/m <sup>2</sup>
Composition:	real wood embossed veneer (3.5-4mm) on a MDF panel (thickness 6mm), grooved on all sides for mounting, counter-veneer
Packaging amount:	1 box = 4 Panels = 1.1m <sup>2</sup>
Bonding:	White glue D3 DIN EN 204 (formaldehyde-free)
Lacquer:	Transparent according to DIN 53160 part 1, 2: no discoloration (step 5); DIN 68861 Part 1C Formulation is free from: Wood preservatives, toxic heavy metals, phthalate plasticizers, formaldehyde, CMR substances Cat. 1A + 1B and volatile halogenated organic compounds.
Installation type:	horizontal or vertical on walls or ceilings, furniture fronts
Assembly:	by means of claws and wooden framework (please see mounting accessories by KOLAR) or permanently elastic adhesive
Application:	For interior use only, use in the damp rooms is not recommended

Manufacturer: Franz Kolar GmbH, [www.kolar.at](http://www.kolar.at)

Product offered: \_\_\_\_\_

Quantity \_\_\_\_\_ m<sup>2</sup>

### Mounting accessories for WALLWOOD (please see also STEPWOOD mounting)

Claw set	(SW.KR)
Mounting profile	(SW.ML)
Skirting	(SW.RL)

As of November 2020