



Harmonisation of natural appearance and design

The STEPWOOD® design panel is a material creatively designed from individual wooden slats which are slotted together to create a special impression of space... STEPWOOD® panels are eye catching due to the differences in the colour and structure of the individual types of timber.

STEPWOOD® panels represent the harmonisation of natural appearance and design. It also has a positive impact on health: it has been scientifically proven that stress levels in rooms with solid wood panelling are significantly lower. The heartbeat calms in these environments because the air in these rooms contains fewer negatively charged ions, which influences the pulse rate. In addition to this, the latest scientific research has also shown that bacteria on a wooden surface dies faster than on, for example, plastics.

STEPWOOD® panels significantly contribute to healthy living.



STEPWOOD® panels are made exclusively of high-quality and slow dried timbers.




No limits are placed on creativity

Due to the high quality of the wood and natural appearance, STEPWOOD® panels are used for fitting out shops and creating room interiors and property furnishing.



Harmonisation of natural appearance and universal use



New use of traditional material

The possibilities of use for carpenters, cabinet makers, shop fitters, architects and planners, interior designers and arrangers are virtually unlimited.





Multifaceted use for furnishing interiors

Depending on the type and structure of timber there is a choice between a rustic or modern design. Our STEPWOOD® fits any environment, no matter whether at home, in a shop, in restaurants or offices.




Mounting - simple, fast and clean

STEPWOOD® panels are suitable for creating interiors. Their fitting depends on the purpose of use and number of panels.

Panels can be glued or screwed to a dry, clean surface.

STEPWOOD® panels can be used on:



STEPWOOD® panels can be laid horizontally and vertically.

An information sheet for the mounting and processing of STEPWOOD® panels is available at www.kolar.at as well as a short installation video

For mounting, we recommend our STEPWOOD® mounting equipment.

We offer skirtings in suitable timber versions and metal claws. You can use our mounting equipment with all STEPWOOD® products except STEPWOOD® Light.





Mounting profile SW ML spruce 50x20 mm



Skirt moulding SW RL for STEPWOOD® Original, 33x8mm



Skirt moulding SWN RL and SW RL Alt for STEP-WOOD® Natural and STEPWOOD® reclaimed lumber



Colour pins SW RL-NAG to fix skirt mouldings



SW KRA (incl. nails)





Connecting claw SW KRV (incl. nails) and wooden tongues SW HF (length 100 mm)

Moulding set SW MLRL

6 pcs.

4 pcs

Length 1.250mm Length 1.250mm

Claw set SW KR

each 3 pcs

20 pcs + 10 pcs 1 claw set is calculated with

STEPWOOD® Original: for 1 box STEPWOOD® reclaimed lumber: 1.5 boxes



panel

STEPWOOD® Natural: 2 boxes

panel

Mounting

profile

Mounting using profiles (spruce), skirt moulding in suitable timber version, and metal claws. Insert the wooden tongues into the grooves for a better stability.

Product facts

STEPWOOD® Original



Technical data:

- Standard panel size: length 1250 x width 219 mm
- Thickness of panel: 12 mm
- Carrier: MDF grooved an all sides
- Surface finish: matt lacquer, unfinished, or oiled
- · Structure: brushed or sanded

Panels are grooved on all sides for a simple mounting with the use of our mounting equipment (see p. 11)



STEPWOOD® LIGHT



Technical data:

- Standard panel size: length 1250 x width 219 mm
- Thickness of panel: 6 mm
- Carrier: fleece
 Surface: unfinished
- · Structure: brushed or sanded







Product facts

STEPWOOD® reclaimed lumber



Technical data:

- Standard panel size: length 1250 x width 220 mm
- Thickness of panel: 17.5 mm

- Carrier: MDF grooved an all sides
- Surface: unfinished
- Structure: naturally weathered

STEPWOOD® Natural



Technical data:

- Standard panel size: length 1250 x width 219 mm
- Thickness of panel: 29 mm

- Carrier: MDF grooved an all sides
- Surface: unfinishedStructure: spilt wood



Sample box, sample folder, and a hand sample – perfectly suitable for planning and for discussions with your customers.







STEPWOOD® Original: standard types of timber

All these timbers are readily available from our warehouse in raw surface or lacquered. Oiled surface on demand.





















STEPWOOD® LIGHT - stock items:

Oak sanded raw SWLEGSR Oak brushed raw SWLEGR Walnut sanded raw SWLNGSR



STEPWOOD® Natural / STEPWOOD® reclaimed lumber







Тур	Panel size L x W in mm	maximum thickness in mm	covered surface per panel in m²	weight per panel in kg	rapport finish	pcs/box	covered surface per box in m²	minimum order quantity	delivery time
STEPWOOD® Original									
Stock items (Standard timbers)	1250 x 219	12	0.274	2.5	on demand	5	1.37	5 panels	on stock
STEPWOOD® Natural									
Oak raw	1250 x 219	29	0.26	3.5	yes	2	0.52	2 panels	on stock
Oak oiled "walnut"	1250 x 219	29	0.26	3.5	yes	2	0.52	2 panels	on stock
STEPWOOD® Light on fleece									
Oak brushed raw	1250 x 219	6	0.274	1.2	-	8	2.19	8 panels	on stock
Oak sanded raw	1250 x 219	6	0.274	1.2	-	8	2.19	8 panels	on stock
Walnut sanded raw	1250 x 219	6	0.274	1.2	-	8	2.19	8 panels	on stock
STEPWOOD® reclaimed lumber									
Spruce sunburnt	1250 x 220	17.5	0.275	3.0	-	3	0.825	3 panels	on stock









FSC certified products

Our production is certified



Franz Kolar Ges.m.b.H.

Josef-Strebl-Gasse 8 · 2345 Brunn/Geb. · AUSTRIA T +43/2236/3 17 24 · F +43/2236/3 23 96 office@kolar.at · www.kolar.at